

# Avionics

## DT600 ARINC 429/629 DATABUS ANALYZER

**AEROFLEX**  
A passion for performance.



A powerful tool that can be used on the ramp or on the bench

The DT600 is a combination ARINC 429/629 databus analyzer with dual, independent ports for each bus standard. Nearly identical functions are provided for each bus type. These include basic receive and transmit functions along with a general record mode and a powerful breakpoint mode. The standard RS-232 port is used for downloading real time or recorded data and for uploading new label/word definitions. The standard DAC port can be used to provide a trigger pulse or to drive recorders or instruments. An optional GPIB port permits remote control of all functions. PC software is available to aid the user in defining customized data definition table(s). The large graphical display and integrated keyboard provide an informative and intuitive user interface.

### FEATURES

- Two ARINC TX/RX ports and two ARINC 629 transceiver ports
- Operates six to eight hours on the internal battery or power from external 28 VDC or 105-250 VAC
- Easy menu-driven setup allows intuitive control of unit
- Multi-window display of data in ENGINEERING (B777 default for 629), HEX, BINARY, USER DEFINED, and GRAPHICAL formats
- Powerful record and fault analyzer modes
- Williamsburg Protocol software extension available for ARINC 429 file transfer functions
- RS-232C and DAC interface ports standard; GPIB optional
- Software available for RS-232 port (download/upload and word definitions)

### GENERAL SPECIFICATIONS

#### ARINC 429 RECEIVER OPERATION

##### Ports

2

##### Bus Frequency

12-14.5 kHz or 100 kHz (selectable)

##### Input Levels

+ 6.5 VDC to + 13.5 VDC (A to B)

##### Input Impedance

12.0 K ohms

##### Word Update

1 ms to 10 sec, update rate displayed as instantaneous, min or max value

##### Display Format

Pre-stored engineering units, hex, binary, user, ASCII, & graphic plots

##### Maximum Words

256 per SDI per channel

##### Bus Activity Monitor

Monitors loss of individual words; sensitivity selectable

##### Real-time Download/Conversion

RS-232C or 12-bit DAC port

#### ARINC 429 TRANSMITTER OPERATION

##### Ports

2

##### Bus Frequency

12.0 kHz, 12.5 kHz, 14.5 kHz, or 100 kHz (selectable)

For the very latest specifications visit [www.aeroflex.com](http://www.aeroflex.com)

### Output Levels

+ 10.0 VDC (A to B)

### Output Impedance

75 ohms

### Word Update

1 ms to 10 sec, (selectable)

### Burst Mode

01 to 99 burst outputs at a selectable rate

### Display Format

Pre-stored engineering units, full or data field hex and binary, user, and ASCII

### Maximum Words

128 per channel

### Transmit Word Gap

2, 3, 4, 5, 6, 8, 12 bits (selectable)

### Dynamic Transmit

Repeat pattern of ramps and flat segments. Levels programmable between + full scale and segment times of 0 to 999.999 sec

### Additional Transmit Options

Recorded data, pre-stored tables

---

## ARINC 429 BREAKPOINT OPERATION

---

### Label Sequence

A, B, A or B, A then B, A immediate B

### Data Conditions

EQ, NEQ, OR, GT, LT, /GT/, /LT/

### Event Count

1 to 99 before break

### History

Up to 24,576 words in a programmable window; optional time stamp

### Trigger Pulse

5V, 20  $\mu$ S

---

## ARINC 429 BITE OPERATION

---

### BITE Formats

Compatible with distributed and centralized BITE concept used on 747-400, 737-300, MD-11, A320, A330, and A340 aircraft

### Menu Display

Standard 14-line x 24-character format, with selectable menu choices

### Maintenance Words

Displays 350/351 label maintenance bits. Bit status along with pre-stored text presented

### Recording Feature

Save up to 240 BITE screens for later viewing or downloading

---

## ARINC 629 RECEIVER OPERATION

---

### Ports

1 standard, 2nd optional

### Bus Frequency

2 MHz

### Input Electrical Characteristics

Doublet as specified for SIM input in the Boeing D227W201 Universal Data Sheet

### Word Update

1 ms to 10 sec, update rate displayed instantaneous, min or max value

### Display Format

Pre-stored engineering units, hex, binary, user, ASCII, & graphic plots

### Word Strings Receivable

4096

### Words Selectable

255 words per word string, 32 word strings

### Bus Activity Monitor

Monitors loss of individual words; monitor sensitivity selectable

### Real-time Download/Conversion

RS-232C or 12-bit DAC port

---

## ARINC 629 TRANSMITTER OPERATION

---

### Ports

1 standard, 2nd optional

### Bus Frequency

2 MHz

### Output Electrical Characteristics

Doublet as specified for SIM output in the Boeing D227W201 Universal Data Sheet

### Transmit Interval

0.5 to 64 ms (selectable)

### Synchronization Gap

16, 32, 64, and 127  $\mu$ S (selectable)

### Terminal Gap

1 to 128  $\mu$ S (selectable)

### Synchronization

C Mode communication provisions with external terminals

### Display Format

Pre-stored engineering units, hex, binary, user, and ASCII

### Maximum Words per Word String

256

### Maximum Word Strings

31 x 31

### Dynamic Transmit

Repeat pattern of ramps and flat segments. Levels programmable between + full scale and segment times of 0 to 999.999 sec

## ARINC 629 BREAKPOINT OPERATION

---

### Label Sequence

A, B, A or B, A then B

### Data Conditions

EQ, NEQ, OR, GT, LT, /GT/, /LT/

### Event Count

1 to 99 before break

### History

Up to 40,960 words in a programmable window; optional time stamp

### Trigger Pulse

5V, 20  $\mu$ S

## ARINC 429/629 RECORD OPERATION

---

### Channels

429: Up to 16 labels from any combination of receive ports

629: Up to 32 data words from any combination of receive ports

### Sample Interval

1 ms to 10 sec (selectable)

### Record Capacity

120 Kbytes

### Playback Options

Graphic plots, data lists, DAC download, RS-232C download

## PHYSICAL CHARACTERISTICS

---

### Weight

24 lbs. (10.9 kg)

### Size

5.7"H x 14.25"W x 12"D (14.5 cm x 36.2 cm x 30.5 cm)

---

## VERSIONS, OPTIONS AND ACCESSORIES

---

When ordering please quote the full ordering number information.

Ordering Number	Description
993	DT600 ARINC 429/629 Databus Analyzer (110/220V)
994	DT600 ARINC 429/629 Databus Analyzer w/ Williamsburg Protocol Analyzer (110/220V)

### Standard Accessories

60492	RS-Read software
58225	RS-232 cable
75641	DT600 Operations Manual (CD)
29979	Cable, BNC male/DBL banana plug
29972	Power cord, 3 cond., 1250 W, 10A, 125V
58226	Cable, ARINC stub

### Optional Accessories

60494	PCMGR-600 Software support for DT600/650/650H
17897	Extender board for DT400/600/650
18057	DT600 2-TX port expansion
18060	DT600 2-RX port, 1-DAC port expansion
18061	DT400/600 IEEE-488 interface board
18070	DT600 transceiver board A629

### Extended Warranty

84381	Extended standard warranty 36 months with scheduled calibration
84382	Extended standard warranty 60 months with scheduled calibration

**CHINA Beijing**

Tel: [+86] (10) 6539 1166  
Fax: [+86] (10) 6539 1778

**CHINA Shanghai**

Tel: [+86] 21 2028 3588  
Fax: [+86] 21 2028 3558

**CHINA Shenzhen**

Tel: [+86] (755) 3301 9358  
Fax: [+86] (755) 3301 9356

**FINLAND**

Tel: [+358] (9) 2709 5541  
Fax: [+358] (9) 804 2441

**FRANCE**

Tel: [+33] 1 60 79 96 00  
Fax: [+33] 1 60 77 69 22

**GERMANY**

Tel: [+49] 89 99641 0  
Fax: [+49] 89 99641 160

**HONG KONG**

Tel: [+852] 2832 7988  
Fax: [+852] 2834 5364

**INDIA**

Tel: [+91] 80 [4] 115 4501  
Fax: [+91] 80 [4] 115 4502

**JAPAN**

Tel: [+81] (3) 3500 5591  
Fax: [+81] (3) 3500 5592

**KOREA**

Tel: [+82] (2) 3424 2719  
Fax: [+82] (2) 3424 8620

**SCANDINAVIA**

Tel: [+45] 9614 0045  
Fax: [+45] 9614 0047

**SINGAPORE**

Tel: [+65] 6873 0991  
Fax: [+65] 6873 0992

**TAIWAN**

Tel: [+886] 2 2698 8058  
Fax: [+886] 2 2698 8050

**UK Stevenage**

Tel: [+44] (0) 1438 742200  
Fax: [+44] (0) 1438 727601  
Freephone: 0800 282388

**USA**

Tel: [+1] (316) 522 4981  
Fax: [+1] (316) 522 1360  
Toll Free: 800 835 2352

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2011.

[www.aeroflex.com](http://www.aeroflex.com)  
[info-test@eroflex.com](mailto:info-test@eroflex.com)



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.